

PRODUCT DATA SHEET



Characteristic	Description
General	
Product Name	REFLECTOMARK RR
Product Type	Acrylic Reflective Paint
Colour	White / Yellow – Reflective Finish
Application	Roller
Physical Characteristics	
Drying Time	5 – 10 Minutes Touch Dry
Consistency	Smooth & Uniform
Coverage	3.5 – 4 m ² / Kg
Packaging	
2 Kg / 5 Kg Standard Packaging	
Storage	
Shelf Life: 12 Months from Manufacturing subject to the material being stored in moisture-free, dry conditions without opening the packaging.	
Areas of Application	
Concrete Kerbs & Crash Barriers	
Application Safeguards	
- The surface to be marked shall be clear of dirt, dust, debris. - Any curing compounds / putty / previous surface coatings must be stripped off prior to application - New Concrete / Asphalt should be allowed to cure for a minimum 20 days to maximize adhesion and durability - Ensure surface ambient temperature is more than 10°C - Use Kataline Trakmark WR as primer application	

ISO 9001 & ISO14001 Certified Manufacturer

Safety Recommendations
• Store in cool dry environment • Avoid contact with eatables. If ingested seek immediate medical attention. • Recommended disposal of empty buckets as per good engineering practices and environmental policies
Post Application Care
For best results ensure traffic is not allowed on the road for an ideal duration of 1 hour after application and complete drying of material.